

Product :	R404A	Page :1/
MSDS Nr : 300-25-0010BOC(A)	Version: 1.03	Date : 02/09/200
I IDENTIFICATION OF THE SUBS	FANCE/PREPARATION AND OF THE COMPANY	
Product name	R404A	
Company identification	see heading and/or footer	
Emergency phone numbers	see heading and/or footer	
2 COMPOSITION/INFORMATION	ON INGREDIENTS	
Substance/Preparation	Preparation	
Components/Impurities	Contains the following components: 52% w/w Trifluoroethane (R143a) {F+	+;R12} {EINECS
	No. 206-996-5}/44% w/w Pentafluoroethane (R125) {EINECS No. 206-55	57-8}/4% w/w
	1,1,1,2-Tetrafluoroethane (R134a) {EINECS No. 212-377-0}	
EC Nr (from EINECS)	Not applicable for preparations	
3 HAZARDS IDENTIFICATION		
Hazards identification	In high concentrations may cause asphyxiation.	
	Liquefied gas	
	Not classified as dangerous preparation.	
4 FIRST AID MEASURES		
Inhalation	In low concentrations may cause narcotic effects. Symptoms may include dia	zziness, headache,
	nausea and loss of co-ordination.	
	In high concentrations may cause asphyxiation. Symptoms may include loss	of
	mobility/consciousness. Victim may not be aware of asphyxiation.	
	Remove victim to uncontaminated area wearing self contained breathing app	paratus. Keep
	victim warm and rested. Call a doctor. Apply artificial respiration if breathin	ng stopped.
Skin/eye contact	In case of frostbite spray with water for at least 15 minutes. Apply a sterile d	ressing.
	Immediately flush eyes thoroughly with water for at least 15 minutes.	
	Obtain medical assistance	
Ingestion	Ingestion is not considered a potential route of exposure.	
5 FIRE FIGHTING MEASURES		
Specific hazards	Exposure to fire may cause containers to rupture/explode.	
	Non flammable	
Hazardous combustion products	If involved in a fire the following toxic and/or corrosive fumes may be produ	aced by thermal
	decomposition:	• ···
	Carbonyl fluoride	

Carbonyl fluoride



Product :	<b>R404</b> A	Page :2/
MSDS Nr : 300-25-0010BOC(A)	Version : 1.03	Date : 02/09/200
	Hydrogen fluoride	
	Carbon monoxide	
Suitable extinguishing media	All known extinguishants can be used.	
Specific methods	If possible, stop flow of product.	
	Move away from the container and cool with water from a protected position.	
Special protective equipment for fire fighters	Use self-contained breathing apparatus and chemically protective clothing.	
ACCIDENTAL RELEASE MEASU	RES	
Personal precautions	Evacuate area.	
	Wear self-contained breathing apparatus when entering area unless atmosphere is	proved to be
	safe.	
	Ensure adequate air ventilation.	
Environmental precautions	Try to stop release.	
	Prevent from entering sewers, basements and workpits, or any place where its acc	umulation
	can be dangerous.	
Clean up methods	Ventilate area.	
HANDLING AND STORAGE		
Handling and storage	Suck back of water into the container must be prevented.	
	Do not allow backfeed into the container.	
	Use only properly specified equipment which is suitable for this product, its supply	y pressure
	and temperature. Contact your gas supplier if in doubt.	
	Refer to supplier's container handling instructions.	
	Keep container below 50°C in a well ventilated place.	

Exposure limit value for country	UK: 1,1,1,2-Tetrafluoroethane (R134a) - LTEL: 1000ppm (EH40/2002)
	UK: Pentafluoroethane (R125) - LTEL: 1000ppm
	UK: Trifluoroethane (R143a) - LTEL: 1000ppm
Personal protection	Ensure adequate ventilation.
	Do not smoke while handling product.
	Protect eyes, face and skin from contact with product.

### 9 PHYSICAL AND CHEMICAL PROPERTIES

Molecular weight

97.6



Product :	R404A	Page :3/3
MSDS Nr : 300-25-0010BOC(A)	Version: 1.03	Date : 02/09/2003
Boiling point	-47 °C	
Critical temperature	72 °C	
Relative density, gas	3.4 (air=1)	
Relative density, liquid	1.07 (water=1)	
Vapour Pressure 20°C	11 bar(a).	
Solubility mg/l water	No reliable data available.	
Appearance/Colour	Colourless gas	
Odour	Ethereal	
	Poor warning properties at low concentrations.	
Other data	Gas/vapour heavier than air. May accumulate in confined spaces, particularly at	or below
	ground level.	
STABILITY AND REACTIVITY		
Stability and reactivity	Stable under normal conditions.	
	Thermal decomposition yields toxic products which can be corrosive in the prese	ence of
	moisture.	
	May react with aluminium.	
TOXICOLOGICAL INFORMATIO	)N	
General	May produce irregular heart beat and nervous symptoms.	
ECOLOGICAL INFORMATION		
General	When discharged in large quantities may contribute to the greenhouse effect.	
Global warming factor	3800 (CO2=1)	
	5000 (CO2-1)	
DISPOSAL CONSIDERATIONS		
General	Avoid discharge to atmosphere.	
	Do not discharge into any place where its accumulation could be dangerous.	
	Refer to supplier's waste gas recovery programme.	
	Contact supplier if guidance is required.	
TRANSPORT INFORMATION		
TRANSPORT INFORMATION Proper shipping name	REFRIGERANT GAS R 404A	



Product :	R404A	Page :4/
MSDS Nr : 300-25-0010BOC(A)	Version : 1.03	Date : 02/09/200
Class	2.2	
ADR/RID Classification code	2A	
ADR/RID Hazard Nr	20	
Labelling ADR	Label 2.2: non flammable non toxic gas	
Other transport information	Avoid transport on vehicles where the load space is not separated from the drive	er's
	compartment.	
	Ensure vehicle driver is aware of the potential hazards of the load and knows w	hat to do in the
	event of an accident or an emergency.	
	Before transporting product containers ensure that they are firmly secured and:	
	- cylinder valve is closed and not leaking	
	- valve outlet cap nut or plug (where provided) is correctly fitted	
	- valve protection device (where provided) is correctly fitted	
	- there is adequate ventilation.	
	- compliance with applicable regulations.	

Number in Annex I of Dir 67/548	Not applicable for preparations
EC Classification	Not classified as dangerous preparation.
Labelling of cylinders	
-Symbols	Label 2.2: non flammable non toxic gas

#### **16 OTHER INFORMATION**

Ensure all national/local regulations are observed.

Contact with liquid may cause cold burns/frost bite.

Asphyxiant in high concentrations.

Keep container in well ventilated place.

Do not breathe the gas.

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Users of breathing apparatus must be trained.

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.



**Product :** 

R404A

Page :5/5 Date : 02/09/2003

MSDS Nr : 300-25-0010BOC(A)

Version: 1.03

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document. Number of pages :5